



# ISV FLOATING BALL VALVES

## Threaded, Socket Weld & Butt-Weld Ends PRODUCT SUMMARY

QUALITY MANAGEMENT SYSTEM  
CERTIFIED BY DNV  
ISO 9001:2008

1/4" - 4" sizes

Pressures up to ASME class 2500 (6000 psig W.O.G.)

- ASME B16.34 compliant valves for full piping system compliance to B31 piping codes
- General industrial ball valves
- *Oilfield* design ball valves
- Competitive Prices
- Stock availability in Houston
- In-house (Houston) pressure testing program
- MTR's available

*Products of Taiwan*



### BF2ER

3 piece Forged Bolted Body,  
Reduce Port



- ASME class 1500 ( 3600 W.O.G.)
- ASME B16.34 /API 608 design, ASME code compliant
- 1/2" - 2" sizes
- A105N, LF2, F316, F316L, F304L body materials
- Threaded, Socket Weld and Nipple Ends

### BF2EF

3 piece Cast Bolted Body,  
Full Port



- ASME class 800 1/2" - 1.25", ( 1.5" - 2" 1500 W.O.G.)
- ASME B16.34 /API 608 design, ASME code compliant
- 1/2" - 2" sizes
- WCB, CF8M, CN7M, Hastelloy, Monel body materials
- Threaded, Socket Weld and Butt-Weld Ends

### I-136 / I-138

3 piece Forged Threaded Body,  
Full & Reduced



- Pressures of 2000, 3000 & 6000 psig W.O.G.
- Rugged *Oilfield* design, tack weld body-tail piece joints
- 1/2" - 3" sizes, ASME B16.34 code compliant
- A105N, LF2, F316, F316L body materials
- Threaded & Socket Weld Ends

### BF2DR

2 piece Seal Weld Body,  
Reduce Port



- ASME class 900 ( 2200 psig WCB, 2160 psig CF8M)
- ASME B16.34 /API 608 design, ASME code compliant
- 1/4" - 2" sizes
- WCB & CF8M body materials
- Threaded Ends

### IA / IC

2 piece Cast Threaded Body,  
Full & Reduced



- Pressures of 750—2500 psig W.O.G.
- Cast heavy duty *Oilfield* design
- 1" - 4" sizes
- WCB, LCC & Ductile Iron body materials
- Threaded end connections

### BFOCF & BFOEF

2 PC & 3 PC Cast Body,  
Full Port



- Pressures of 800—1000 psig W.O.G.
- 2PC threaded & 3 PC bolted body designs
- 1/4" - 4" sizes
- WCB, CF8M, CN7M, Hastelloy, Monel body materials
- Threaded, Socket Weld and Butt-Weld Ends

